



THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.  
COPY RIGHT@2020 RION TECHNOLOGY



### Electrical Specification

1 Rings	24	2 Current	Signal module:24rings, MAX:2A/ring
2 Voltage	0-120VDC/VAC		
3 Insulation Resistance	100MΩ@150VDC		
4 Electrical noise	Max.10mΩ;		
5 Dielectric strength	100VAC@50Hz;60S		

### Mecchanical Specification

6 Speed	0~250RPM;	7 Torque	Max.0.2 N.M;
8 Life	Typical 10million revolutions, but strongly depends on your working conditions		

### Environmental adaptability

9 Working temperature	-40℃~+80℃	10 Storage temperature	-45℃~+85℃
11 humidity	85±3%(30℃+5℃)		
12 Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times		
13 IP Class	IP51		

UNLESS OTHERWISE SPECIFIED		TOLERANCES (EXCEPT AS NOTED)		24 rings 2A Signal	
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR 2.MATERIAL &FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		DECIMAL	X±.1 XX±.03 XXX±.005	MODEL	RC400-S24
FILLETs R.015	FINISH			SIZE	A
THIRD ANGLE PROJECTION		FRACTIONAL	1/16	R.E.V.	A / 0
		ANGULAR	±1°	SCALE	1:1
		UNIT	mm	UNIT	mm



### Materral/Attachment

14 Contact Material	noble metal	15 Housing material	engineering plastic
16 Lead wire	Rotor:300mm(See wiring diagram) Stator:300mm(See wiring diagram)		