THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST, THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION, THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT. COPY RIGHT@2020 RION TECHNOLOGY 121.5 92 36.8 4-G1/8" Rotor Port 21 Ø56<sub>0</sub> 4-G1/8" Stator Port 19 4-M5 DP 10 Stator wires Ø45 9\*3=27 Rotor wires/ <del>7</del>8 2-M5 DP 8 EQS Stator fixed hole Rotor side | Stator side Technical parameters of rotary joint 1 Pressure Max 1 Mpa 2 Passage 4 passage Air 3 Texture of materia Aluminium alloy G1/8" 4 Tracheal connector 18 Rings Signal Media type Compressed air 18-AWG28# teflon **Electrical Specification** 2 Current 1 Rings Signal module:18 rings signal 3 Voltage 0-120VDC/VAC 4 Insulation Resistance 100MΩ@150VDC 5 Electrical noise Max.10mΩ; 6 Dielectric strength 500VAC@50Hz;60S Mechanical Specification 7 Speed 0~250RPM; 8 Torque Max.0.9 N.M; Life 10million revolutions, but strongly depends on your working conditions 9 Typical **Environmental adaptability** 10 Working temperature |-30°C~+80°C 11 Storage temperature -35℃~+85℃ 12 humidity 85±3%(30℃+5℃) 13 Rush 40g,11ms,Half sine wave, Vertical direction 3 times, Level 3times UNLESS OTHERWISE SPECIFIED 4 passage Air + 18 rings signal TOLERANCES EXCEPT AS NOTE 14 IP Class IP51 1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR 2.MATERIAL&FINISH TO BE AS NOTED OR RKD41S-S18 MODEL SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT DECIMAL X±.1 Material/Attachment XX±.03 FILLETS R.015 FINISH 🤝 XXX±.00 16 Housing material ALL Alloy 15 Contact Material Precious metal RACTIONAL±1/16 THIRD ANGLE PROJECTION 17 Lead wire Rotor:300mm(See wiring diagram) ANGULAR±1° ⊕ 母 Stator:300mm(See wiring diagram)