


132.1



UNLESS OTHERWISE SPECIFIED 1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES & BEBURR 2.MATERIAL & FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		TOLERANCES	4 passage Air + 24 rings signal			
		EXCEL TAGNOTED)	MODEL	RKD41S-S24	4	
		DECIMAL X±.1 XX±.03			SIZE	Α
FILLETS R.015	FINISH [™]	XXX±.005			R E V.	A/0
THIRD ANGLE PROJECTION		FRACTIONAL±1/16		SCA		1:1
		ANGULAR±1°	_		UNIT	mm

Technical parameters of rotary joint

	1	Pressure	Max 1 Mpa	2	Passage	4 passage Air
	3	Texture of materia	Aluminium alloy	4	Tracheal connector	G1/8"
l	5	Media type	Compressed air			

Electrical Specification

1	Rings	24	2	Current	Signal module:24 rings signal
ω	Voltage	0-120VDC/VAC			Olgridi Moddie:24 migo Signal
4	Insulation Resistance	100MΩ@150VDC]		
5	Electrical noise	Max.10mΩ;			
6	Dialoctric strongth	FOOMA CONTOURNED	1		

Mechanical Specification

	7	Speed	0~250RPM;	8	Torque	Max.0.9 N.M;
Γ	9	Typical Life	10million revolutions	, bı	ut strongly	depends on your working conditions

Environmental adaptability

10	Working temperature	-30℃~+80℃	11	Storage temperature	-35℃~+85℃
12 humidity		85±3%(30℃+5℃)			
13	Rush	40g,11ms,Half sine wave,			
		Vertical direction 3 tim	es,L	evel 3times	
14	IP Class	IP51			

Material/Attachment

	<u></u>								
1	5 Contact Material	Precious metal	16	Housing material	ALL Alloy				
1	7 Lead wire	vire Rotor:300mm(See wiring diagram)							
		Stator:300mm(See wiring diagram)							