


THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORISED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2020 RION TECHNOLOGY



UNLESS OTHERWISE SPECIFIED		16 passage Gas	
1. ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES & DEBURR		TOLERANCES (EXCEPT AS NOTED)	
2. MATERIAL & FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		MODEL	RQR16
FILLETS R.015	FINISH \checkmark	DECIMAL	X±.1 XX±.03 XXX±.005
THIRD ANGLE PROJECTION		RION	
ANGULAR±1°		SIZE	A
		RE V.	A / 0
		SCALE	1:1
		UNIT	mm

Technical parameters of rotary joint					
1	Pressure	Max 1 Mpa	2	Passage	16 passage Gas
3	Torque	Max.1.5 N.M;	4	Tracheal connector	M5
5	Media type	Compressed air	6	Working temperature	-30°C~+80°C
7	Speed	0-100RPM	8	Storage temperature	-35°C~+85°C
9	Housing material	ALL Alloy			