




THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.  
COPY RIGHT@2023 RION TECHNOLOGY



### Electrical Specification

1	Rings	6	2	Current	Signal module: 6 rings signal
2	Voltage	0-440VAC/VDC			
3	Insulation Resistance	800MΩ@600VDC			
4	Electrical noise	Max.10mΩ;			
5	Dielectric strength	600VAC@50Hz;60S			

### Mechanical Specification


6	Speed	0~2500RPM;	7	Torque	Max.0.5 N.M;
---	-------	------------	---	--------	--------------

### Environmental adaptability

9	Working temperature	-30℃~+80℃	10	Storage temperature	-30 ~+80
11	humidity	85±3%(30℃+5℃)			
12	Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times			
13	IP Class	IP51			

### Material/Attachment

14	Contact Material	noble matal	15	Housing material	ALL Alloy
16	Lead wire	Rotor: (See wiring diagram) Stator: (See wiring diagram)			



UNLESS OTHERWISE SPECIFIED		6 rings signal	
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR		TOLERANCES (EXCEPT AS NOTED)	
2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		MODEL	RT07506HS-0006-2500RPM
FILLETES R.015	FINISH $\sqrt{\text{V}}$	DECIMAL	X±.1 XX±.03 XXX±.005
THIRD ANGLE PROJECTION		FRACTIONAL±1/16	SIZE A
		ANGULAR±1°	R E V. A / 0
DWG.NO	FSD	DATE	2022-11-09
		SCALE	1:1
		UNIT	mm