THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD (HEREAFTER"RION"), IT IS LENT AND IS TO BE RETURNED UPON REQUEST, THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION, THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT. COPY RIGHT@2020 RION TECHNOLOGY Rotor side [∧] Stator side 3-Ø**5.4(**TH**)EQS** Ø44.8 Stator wires Rotor wires Ø35 8 Ø9.9 36 45 **Electrical Specification** 2 Rings 20A 2-AWG14# teflon 1 Rings 2 Current Power module: 2rings ,20A/ring 3 Voltage 0-380VDC/VAC 4 Insulation Recistance 500MΩ@500VDC 5 Electrical noise Max.10mΩ; 6 Dielectric strength 500VAC@50Hz;60S Mecchanical Specification 0~250RPM; 7 Speed 8 Torque Max.0.2 N.M; Typical: 10million revolutions, but strongly depends on your working conditions 9 Life Environmental adaptability 10 Working temperature -30°C~+80°C 11 Storage temperature -35℃~+85℃ 12 humidity 85±3%(30℃+5℃) 13 Rush 40g,11ms,Half sine wave, Vertical direction 3 times, Level 3times UNLESS OTHERWISE SPECIFIED 2 rings 20A TOLERANCES EXCEPT AS NOTE 14 IP Class IP51 1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR 2.MATERIAL&FINISH TO BE AS NOTED OR RW1220 MODEL SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT DECIMAL X±.1 Materal/Attachment XX±.03 FILLETS R.015 FINISH ¹²⁵✓ XXX±.00 15 Contact Material Precious metal 16 Housing material | Engineering plastic RACTIONAL±1/16 THIRD ANGLE PROJECTION 17 Lead wire Rotor:300mm(See wiring diagram) ANGULAR±1° ⊕ 母 Stator:300mm(See wiring diagram)