



THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2020 RION TECHNOLOGY



Electrical Specification

1 Rings	5	2 Current	Power module:4 rings, 10A/ring 1 ring, shield
2 Voltage	0-440VDC/VAC		
3 Insulation Resistance	500MΩ@1000VDC		
4 Electrical noise	Max.10mΩ;		
5 Dielectric strength	1000VAC@50Hz;60S		

Mecchanical Specification

6 Speed	0~250RPM;	7 Torque	Max.0.2 N.M;
8 Life	Typical 30million revolutions, but strongly depends on your working conditions		

Environmental adaptability

9 Working temperature	-40℃~+80℃	10 Storage temperature	-45℃~+85℃
11 humidity	85±3%(30℃+5℃)		
12 Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times		
13 IP Class	IP51		

Materral/Attachment

14 Contact Material	noble metal	15 Housing material	AL Alloy+engineering plastic
16 Lead wire	Rotor:1000mm(See wiring diagram) Stator:1500mm(See wiring diagram)		

UNLESS OTHERWISE SPECIFIED		TOLERANCES (EXCEPT AS NOTED)		4 rings 10A +1 ring shield	
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES SDEBURR		DECIMAL X±.1 XX±.03 XXX±.005		MODEL RX00709005	
FILLETS R.015	FINISH ✓		SIZE	A	
THIRD ANGLE PROJECTION			REV.	A / 0	
ANGULAR±1°			SCALE	1:1	
			UNIT	mm	