THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2020 RION TECHNOLOGY





Electrical Specification

1	Rings	48	2	Current	Power module: 9 rings, 10A/ring Signal module: 39 rings,MAX:5A/ring
3	Voltage	0-380VDC/VAC			
4	Insulation Recistance	500MΩ@500VDC			
5	Electrical noise	Max.10mΩ;			
6	Dielectric strength	500VAC@50Hz;60S			

Mecchanical Specification

7	Speed	0~150RPM;	8	Torque	Max.0.2 N.M;
9	Life Typical:	15million revolutions, but strongly depends on your working conditions			

Environmental adaptability

10	Working temperature	-30℃~+80℃	11	Storage temperature	-35℃~+85℃
12	humidity	85±3%(30℃+5℃)			
13	Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times			
14	IP Class	IP51			

Materal/Attachment

15	Contact Material	Precious metal	16	Housing material	**ALL Alloy**
17	Lead wire	Rotor:300mm(See wiring diagram) Stator:300mm(See wiring diagram)			

UNLESS OTHERWISE SPECIFIED 1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR 2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT FILLETS R.015 FINISH THIRD ANGLE PROJECTION	TOLERANCES (EXCEPT AS NOTED) DECIMAL X±.1 XX±.03 XXX±.005 FRACTIONAL±1/16 ANGULAR±1°	9 rings 10A+39 rings Signal MODEL RX00723001 RION	SIZE A REV. A/0 SCALE 1:1 UNIT mm