




THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2020 RION TECHNOLOGY



UNLESS OTHERWISE SPECIFIED		3rings 10A+2 Channel 1000M Ethernet Signal	
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES & DEBURR		TOLERANCES (EXCEPT AS NOTED)	
2.MATERIAL & FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		MODEL RX00727003	
DECIMAL X±.1 XX±.03 XXX±.005		SIZE	A
FILLETS R.015	FINISH ✓	REV.	A / 0
THIRD ANGLE PROJECTION		SCALE	1:1
ANGULAR±1°		UNIT	mm

Electrical Specification			
1 Rings	21	2 Current	Power module:3 rings; 10A/ring
3 Voltage	0-440VDC/VAC	Signal module:18 rings	
4 Insulation Resistance	1000MΩ@1000VDC		
5 Electrical noise	Max.10mΩ;		
6 Dielectric strength	1000VAC@50Hz;60S		

Mechanical Specification			
7 Speed	0~250RPM;	8 Torque	Max.0.2N.M;
9 Life	Typical :10million revolutions, but strongly depends on your working conditions		

Environmental adaptability			
10 Working temperature	-30℃~+80℃	11 Storage temperature	-35℃~+85℃
12 humidity	85±3%(30℃+5℃)		
13 Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times		
14 IP Class	IP51		

Material/Attachment			
15 Contact Material	noble metal	16 Housing material	ALL Alloy
17 Lead wire	Rotor:1000mm(See wiring diagram) Stator:1000mm(See wiring diagram)		