THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2020 RION TECHNOLOGY



UNLESS OTHERWISE SPECIFIED	2 passage Gas
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR 2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT	MODEL: RX00805002
FILLETS R.015 / FINISH	SIZE: A
THIRD ANGLE PROJECTION	R E V.: A / 0
TOLERANCES (EXCEPT AS NOTED) DECIMAL X±.1 XX±.03 XXX±.005 FRACTIONAL±1/16 ANGULAR±1°	SCALE: 1:1
RION	UNIT: mm

Technical parameters of rotary joint

1	Pressure	Max 1 Mpa	2	Passage	2 passage Gas
3	Torque	Max.30N.M;	4	Tracheal connector	G1/8"
5	Media type	Compressed air	6	Working temperature	-40℃~+80℃
7	Speed	0-60RPM	8	Storage temperature	-45℃~+85℃
9	Housing material	ALL Alloy	10	IP Class	IP65
11	Life	Typical: 2million revolutions, but strongly depends on your working conditions			