



THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.  
COPY RIGHT@2020 RION TECHNOLOGY



### Electrical Specification

1 Rings	30	2 Current	Power module:8 rings, 40A/ring Signal module:22 rings
3 Voltage	0-380VDC/VAC		
4 Insulation Resistance	500M $\Omega$ @500VDC		
5 Electrical noise	Max.10m $\Omega$ ;		
6 Dielectric strength	500VAC@50Hz;60S		

### Mechanical Specification

7 Speed	0~250RPM;	8 Torque	Max.0.2 N.M;
9 Life	Typical:20million revolutions, but strongly depends on your working conditions		

### Environmental adaptability

10 Working temperature	-30 $^{\circ}$ C~+80 $^{\circ}$ C	11 Storage temperature	-35 $^{\circ}$ C~+85 $^{\circ}$ C
12 humidity	85 $\pm$ 3%(30 $^{\circ}$ C+5 $^{\circ}$ C)		
13 Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times		
14 IP Class	IP51		

### Material/Attachment

15 Contact Material	Precious metal	16 Housing material	ALL Alloy
17 Lead wire	Rotor:300mm(See wiring diagram) Stator:300mm(See wiring diagram)		

UNLESS OTHERWISE SPECIFIED		8 rings 40A+22 rings signal	
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR		TOLERANCES EXCEPT AS NOTED:	
2.MATERIAL &FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		MODEL	RX00812006
FILLETS R.015	FINISH $\checkmark$	DECIMAL	X $\pm$ .1 XX $\pm$ .03 XXX $\pm$ .005
THIRD ANGLE PROJECTION		SIZE	A
		RE V.	A / 0
		SCALE	1:1
		UNIT	mm

