



THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2020 RION TECHNOLOGY



Technical parameters of rotary joint

1 Pressure	Max 0.8 Mpa	2 Passage	2 passage Air
3 Texture of material	Al alloy+carbon steel	4 Tracheal connector	G3/8"
5 Media type	Compressed air		

Electrical Specification

1 Rings	48	2 Current	Power module:23 rings;10A/ring Signal module:20 Rings Signal + 1 channel Industrial Ethernet
3 Voltage	0-440VDC/VAC		
4 Insulation Resistance	500MΩ@500VDC		
5 Electrical noise	Max.10mΩ;		
6 Dielectric strength	500VAC@50Hz;60S		

Mechanical Specification

7 Speed	0~250RPM;	8 Torque	Max.0.5 N.M;
9 Typical Life	10million revolutions, but strongly depends on your working conditions		

Environmental adaptability

10 Working temperature	30℃~+80℃	11 Storage temperature	-35℃~+85℃
12 humidity	85±3%(30℃±5℃)		

13 Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times
14 IP Class	IP51

Material/Attachment

15 Contact Material	noble metal	16 Housing material	AL Alloy
17 Lead wire	Rotor:(See wiring diagram) Stator:(See wiring diagram)		

UNLESS OTHERWISE SPECIFIED		23 Rings 10A + 20 Rings Signal + 1 channel Industrial Ethernet	
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR		TOLERANCES (EXCEPT AS NOTED)	
2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		MODEL RX01225005	
DECIMAL Xx.1 XXx.03 XXXx.005		SIZE	A
FILLET R.015	FINISH	RE.V.	A/0
THIRD ANGLE PROJECTION		SCALE	1:1
ANGULAR±1°		UNIT	mm