


THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2026 RION TECHNOLOGY



Electrical Specifications

1	Rings	1	2	Current	Power module: 1 Ring 300A
3	Voltage	0~380VAC / VDC			
4	Insulation Resistance	≥500MΩ@500VDC			
5	Electrical noise	Max.20mΩ			
6	Dielectric strength	500VAC@50Hz:60s			

Mechanical Specification

7	Speed	0~1000 rpm	8	Torque	MAX 2 N·m
9	Life	100 million revolutions			

Environmental adaptability

10	Working temperature	-30℃~+80℃	11	Storage temperature	-35℃~+85℃
12	Humidity	85±3%RH(30℃+5℃)			
13	Shock	40g,11ms,Half sine wave, Vertical 3 times,Horizontal 3 times			
14	IP rating	IP51			

Material/Attachment

15	Contact Material	Noble metal	16	Housing material	Al alloy (Hard Anodizing)
17	Lead wire	Rotor:(See wiring diagram) Stator:(See wiring diagram)			