



MARK	ECN NO.	Modify	Approve	DATE

THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2026 RION TECHNOLOGY



Optical fiber			
1 Fiber Type	Single Mode Fiber	2 Wavelength	1310~1550nm
3 Insertion loss	<1.2dB	4 Return loss	≥55dB
5 Max Speed	100rpm	6 Work temperature	-30°C ~+ 80°C
7 Connector Type	LC/UPC	8 Fiber length	See wiring diagram
UNLESS OTHERWISE SPECIFIED 1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR. 2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT.			
TOLERANCES (EXCEPT AS NOTED) SIZE RANGE TOLERANCE X < 6 ±0.1 6 ≤ X < 30 ±0.2 30 ≤ X < 120 ±0.3 120 ≤ X < 400 ±0.5 400 ≤ X < 1000 ±0.8 1000 ≤ X ±1.2		2 Rings 30A + 12 Rings 5A MODEL RX26081701	
FILLETS R.015 FINISH ✓ THIRD ANGLE PROJECTION		RIONSR SIZE A R E V. A / 0 SCALE 1:1 UNIT mm	
FRACTIONAL±1/16 ANGULAR±1° (4,4)			

Electrical Specifications

1 Rings	14	2 Current	Power module: 2 Rings 30A + 12 Rings 5A
3 Voltage	0~300VAC / VDC		
4 Insulation Resistance	≥500MΩ@500VDC		
5 Electrical noise	Max.10mΩ		
6 Dielectric strength	500VAC@50Hz;60s		

Mechanical Specification

7 Speed	0~100 rpm	8 Torque	MAX 0.2 N·m
---------	-----------	----------	-------------

Environmental adaptability

9 Working temperature	-30°C ~+80°C	10 Storage temperature	-35°C ~+85°C
11 Humidity	85±3%RH(30°C+5°C)		
12 Shock	40g, 11ms, Half sine wave, Vertical 3 times, Horizontal 3 times		
13 IP rating	IP51		

Material/Attachment

14 Contact Material	Noble metal	15 Housing material	Al alloy
16 Lead wire	Rotor:(See wiring diagram) Stator:(See wiring diagram)		