


THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2026 RION TECHNOLOGY



1 Pressure	≤ 1 MPa	2 Passage	6 Passage
3 Torque	Max. 3 N·m	4 Tracheal connector	M5
5 Media type	Compressed Air	6 Working temperature	-30℃~+80℃
7 Speed	0~150 rpm	8 Storage temperature	-35℃~+85℃
9 Texture of material	Al alloy		

UNLESS OTHERWISE SPECIFIED		TOLERANCES (EXCEPT AS NOTED)		4 Rings signals MODEL RX26090104	
1. ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES & DEBURR. 2. MATERIAL/FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT.		SIZE RANGE	TOLERANCE		
FILLETS R.0.15 FINISH					
THIRD ANGLE PROJECTION		FRACTIONAL 1/16		SIZE	A
		ANGULAR ±1° (3,3)		RE V.	A / O
				SCALE	1:1
				UNIT	mm

1	Rings	4	2	Current	Signal module: 4 Rings signals
3	Voltage	0~300VAC / VDC			
4	Insulation Resistance	≥500MΩ@500VDC			
5	Electrical noise	Max.10mΩ			
6	Dielectric strength	500VAC@50Hz;60s			

9	Working temperature	-30℃~+80℃	10	Storage temperature	-35℃~+85℃
11	Humidity	85±3%RH(30℃+5℃)			
12	Shock	40g, 11ms, Half sine wave, Vertical 3 times, Horizontal 3 times			
13	IP rating	IP51			

14	Contact Material	Noble metal	15	Housing material	Al alloy
16	Lead wire	Rotor:(See wiring diagram) Stator:(See wiring diagram)			