


THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2026 RION TECHNOLOGY



UNLESS OTHERWISE SPECIFIED		TOLERANCES (EXCEPT AS NOTED)		2 Rings 10A + 2 Rings signals			
1. ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES & DEBURR.		SIZE RANGE	TOLERANCE	MODEL	RX26101006		
2. MATERIAL & FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT.		X < 6	±0.1				
		6 ≤ X < 30	±0.2				
		30 ≤ X < 120	±0.3				
		120 ≤ X < 400	±0.5				
		400 ≤ X < 1000	±0.8				
FILETS R.015		1000 ≤ X	±1.2				
FINISH 		FRACTIONAL ±1/16		SIZE		A	
THIRD ANGLE PROJECTION 		ANGULAR ±1°		R.E.V.		A/0	
		(0,0)		SCALE		1:1	
				UNIT		mm	

Electrical Specifications

1	Rings	4	2	Current	Power module: 2 Rings 10A
3	Voltage	0~380VAC / VDC			
4	Insulation Resistance	$\geq 500\text{M}\Omega @ 500\text{VDC}$			signal module: 2 Rings signals
5	Electrical noise	Max. 10m Ω			
6	Dielectric strength	500VAC@50Hz;60s			

Mechanical Specification

7	Speed	0~250 rpm	8	Torque	MAX 0.5 N·m
---	-------	-----------	---	--------	-------------

Environmental adaptability

9	Working temperature	-30℃~-+150℃	10	Storage temperature	-35℃~-+155℃
11	Humidity	85±3%RH(30℃+5℃)			
12	Shock	40g, 11ms, Half sine wave, Vertical 3 times, Horizontal 3 times			
13	IP rating	IP51			

Material/Attachment

14	Contact Material	Noble metal	15	Housing material	Al alloy + Engineering plastic
16	Lead wire	Rotor:(See wiring diagram) Stator:(See wiring diagram)			