

MARK	ECN NO.	Modify	Approve	DATE

THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2026 RION TECHNOLOGY





Electrical Specifications

1	Rings	4	2	Current	Signal module: 4 Rings signals
3	Voltage	0~120VAC/VDC			
4	Insulation Resistance	⩾100MΩ@100VDC			
5	Electrical noise	Max.10mΩ			
6	Dielectric strength	100VAC@50Hz;60s			

Mechanical Specification

7	Speed	0~100 rpm	8	Torque	MAX 0.1 N·m

Environmental adaptability

9	Working temperature	-40℃~+60℃	10	Storage temperature	-45℃~+65℃
11	Humidity	85±3%RH(30℃+5℃)			
12	Shock	40g,11ms,Half sine wave, Vertical 3 times,Horizontal 3 times			
13	IP rating	IP51			

Material/Attachment

14	Contact Material	Noble metal	15	Housing material	Al alloy + Engineering plastic
16	Lead wire	Rotor:(See wiring diagram) Stator:(See wiring diagram)			

UNLESS OTHERWISE SPECIFIED

1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR.

2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT.

FILLETS R.015 FINISH

THIRD ANGLE PROJECTION

TOLERANCES (EXCEPT AS NOTED)

SIZE RANGE	TOLERANCE
X < 6	±0.1
6 ≤ X < 30	±0.2
30 ≤ X < 120	±0.3
120 ≤ X < 400	±0.5
400 ≤ X < 1000	±0.8
1000 ≤ X	±1.2

FRACTIONAL±1/16
ANGULAR±1°
(6,6)

4 Rings signals

MODEL RX26102208

RIONSR

SIZE	A
REV.	A / 0
SCALE	1:1
UNIT	mm