



THIS DOCUMENT IS THE PROPERTY OF RION TECHNOLOGY(SHENZHEN) LTD.(HEREAFTER"RION"),IT IS LENT AND IS TO BE RETURNED UPON REQUEST,THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO RION,THIS DOCUMENT NOR ITS CONTENTS DOCUMENT NOR ITS CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIAED PERSON COPIED OR PUBLISHED WITHOUT RION PRIOR WRITTEN CONSENT.
COPY RIGHT@2023 RION TECHNOLOGY



Electrical Specification					
1	Rings	80	2	Current	Power module: 80 rings signal
2	Voltage	0-240VAC/VDC			
3	Insulation Resistance	500MΩ@500VDC			
4	Electrical noise	Max.10mΩ;			
5	Dielectric strength	500VAC@50Hz;60S			
Mechanical Specification					
6	Speed	0~250RPM;	7	Torque	
Environmental adaptability					
9	Working temperature	-30℃~+80℃	10	Storage temperature	-30℃~+100℃
11	humidity	85±3%(30℃+5℃)			
12	Rush	40g,11ms,Half sine wave, Vertical direction 3 times,Level 3times			
13	IP Class	IP51			
Material/Attachment					
14	Contact Material	noble matal	15	Housing material	ALL Alloy
16	Lead wire	Rotor: (See wiring diagram) Stator:(See wiring diagram)			



UNLESS OTHERWISE SPECIFIED		TOLERANCES (EXCEPT AS NOTED)		80 rings signal			
1.ALL DIMENSIONS ARE IN MM HES BREAK SHARP EDGES &DEBURR		DECIMAL X±.1		MODEL	RZ130-S80		
2.MATERIAL&FINISH TO BE AS NOTED OR SUBSTITUTED WITH AN APPROVED AND TESTED EQUIVALENT		XX±.03			SIZE	A	
FILLETS R.015 FINISH ✓		XXX±.005			RE V.	A / 0	
THIRD ANGLE PROJECTION		FRACTIONAL±1/16		SCALE	1:1		
ANGULAR±1°		DWG.NO	FSD	DATE	2022-11-09	UNIT	mm